

```
#####  
#          cs315 Week 10  
#  
#  -> 2 dimensional arrays (or matrix)  
#  
#####
```

* Multidimensional arrays

- * arrays so far have been 1 dimensional (flat)
 - > need 1 index to access an element
- * multidimensional arrays use multiple indices to access elements
- * we will focus on 2-dimensional arrays (matrices)
 - > Need 2 indices to access an element
- * Note: 'dimension' here refers to the size of the array not 'dimension' in the mathematical/spatial sense
- * Important:
 - > 1 dimensional arrays needed a base address and length to be complete
 - > 2 dimensional arrays need a base address height and width to be complete

* Matrices

- * represented as a 2 dimensional array
- * size of a matrix is specified with HEIGHT first and WIDTH second
 - > Ex. (7, 12) specifies a matrix which is 7 rows high and 12 columns wide
- * indices are given with the ROW first and COLUMN second
 - > Ex. (2, 5) is the index for row 2 and column index 5

* Storage orders

- * row major - stores array as a sequence of rows
 - > used in Java, C/C++, Python, etc.
 - * column major - stores array as a sequence of columns
 - > used in Fortran, MATLAB, etc.
- > Ex: 4 X 3 matrix

```
+-----+-----+-----+  
| 17  | 21  | 32  |  
+-----+-----+-----+  
| 47  | 51  | 68  |  
+-----+-----+-----+  
| 72  | 89  | 90  |  
+-----+-----+-----+  
| 104 | 117 | 121 |  
+-----+-----+-----+
```

- * when stored as row major, memory is:
 - > 17, 21, 32, 47, 51, 68, 72, 89, 90, 104 117 121
- * when stored as column major, memory is:
 - > 17, 47, 72, 104, 21, 51, 89, 117, 32, 68, 90, 121

* Address calculation

- * address calculations are affected by storage order

--> storage order must be known when calculating addresses
 * the same general equation is used to calculate addresses for both storage orders but use of the variables differs
 * indices here are 0 indexed
 --> (0 0) is the upper left element
 --> for a M x N matrix (M-1, N-1) is the bottom right element

--> equation: $i = b + s * (e*k + n')$
 --> variables:

variable	row major	column major
b	base address	base address
s	element size	element size
e	width (number of columns)	height (number of rows)
k	row index	column index
n'	column index	row index

--> example: if the matrix above is a matrix of words whose base address is 0x10040000 calculate the address of (2, 1) (element value 89)

~ row major:

* e = 3
 * k = 2
 * n' = 1
 * $i = 0x1004\ 0000 + 4 * (3*2 + 1) = 0x1004\ 0000 + 2810 = 0x10040000 + 0x1C = 0x1004\ 001C$

~ column major:

* e = 4
 * k = 1
 * n' = 2
 * $i = 0x1004\ 0000 + 4 * (4*1 + 2) = 0x1004\ 0000 + 2410 = 0x10040000 + 0x18 = 0x1004\ 0018$

+-----+
 | Reminder: Do not mix hexadecimal and decimal arithmetic! |
 +-----+

* Note:

--> for 1 dimensional arrays address calculation is $i = b + s*n$
 --> for 2 dimensional arrays n becomes $(e*k + n')$
 --> all multidimensional arrays are stored in a 1 dimensional memory therefore address calculations for multidimensional arrays must eventually be reduced to a 1 dimensional address calculation

Program example: calculate an address in a column-major matrix of words

```
# $t0 - base address (b)
# $t1 - height (e)
```

```

# $t2 - width
# $t3 - row index (n')
# $t4 - column index (k)
# $t5 - index address (i, to be calculated)
# words are 4 bytes each, therefore s = 4

```

```

-->
mul $t5 $t1 $t4 # $t5 <-- e*k
add $t5 $t5 $t3 # $t5 <-- e*k + n'
sll $t5 $t5 2 # $t5 <-- s*(e*k + n')
add $t5 $t0 $t5 # $t5 <-- b + s*(e*k + n')

```

```

<--
# $t5 is now the address of element ($t3 $t4)

```

```

+-----+
| base addresses are in HEX (base 16) |
+-----+

```

Assume array base address for the following >>=>> 0x1000 BC0C

- 1) address of 9th element if each array element takes 1 byte
in 1 dimensional array (regular array) = array base address + size * index
size * index in decimal = 1 * 8 = 8
size * index in base 16 = 0x0000 0008

```

      1
0x1000 BC0C
+
      8
-----
0x1000 BC1(20)

```

%16 0x1000 BC14 <-- result

- 2) address of 9th element if each array element takes 2 byte
in 1 dimensional array (regular array) = array base address + size * index
size * index in decimal = 2 * 8 = 16
size * index in base 16 = 0x0000 0010

```

0x1000 BC0C
+
      10
-----
0x1000 BC1C <-- result

```

- 3) address of 9th element if each array element takes 4 byte
in 1 dimensional array (regular array) = array base address + size * index

size * index in decimal = 4 * 8 = 32
 size * index in base 16 = 0x0000 0020

```

0x1000 BC0C
+         20
-----
0x1000 BC2C    <-- result

```

- 4) address of 9th element if each array element takes 8 byte
 in 1 dimensional array (regular array) = array base address + size * index
 size * index in decimal = 8 * 8 = 0x0000 0064
 size * index in base 16 = 40

```

0x1000 BC0C
+         40
-----
0x1000 BC4C    <-- result

```

- 5) if 18 bytes structure is being stored (each element is 1 byte). The address of the next element that would be in * word boundary *
 in 1 dimensional array (regular array) = array base address + size * index

```

0x1000 BC0C:  _x_|_x_|_x_|_x_
0x1000 BC10:  _x_|_x_|_x_|_x_
0x1000 BC14:  _x_|_x_|_x_|_x_
0x1000 BC18:  _x_|_x_|_x_|_x_
0x1000 BC1C:  _x_|_x_|_w_|_w_ <<< 'w' <--> waste
0x1000 BC20:  ___|___|___|___
                ^
            start of word boundary

```

* we waste 2 bytes and store the next element in the start of word boundary

20 is divisible by 4 (18 < 20 and 20 % 4 = 0)
 20 in base 16 = 0x0000 0014

```

          1
0x1000 BC0C
+         14
-----
0x1000 BC2(16)

%16    0x1000 BC20    <-- result

```

- 6) in 2 dimensional array of integers (4 bytes)

Given:

50 rows <--> height
100 columns <--> width

Essentially, in a simple language:

row major = base address + size * (width * row index + column index) <-- in row major, we are concerned about number of rows to skip
 [^] [^]
 hex (base 16) base 16 addition

column major = base address + size * (height * column index + row index) <-- in column major, we are concerned about number of columns to skip
 [^] [^]
 hex (base 16) base 16 addition

Order of numbers:

(10, 15)
 [^] [^]
row index column index

a) address of (10, 15) in row major:

0x1000 BC0C + 4 * (100 * 10 + 15)
0x1000 BC0C + 4 * (1015)
0x1000 BC0C + 4060

4060 in base 16 = 0x000 0FDC

4060 | 12 (C) [^]
253 | 13 (D) [^]
15 | 15 (F) [^] rewrite from bottom to up
0 |

 1 1
0x1000 BC0C
+ FDC

0x1000 C(27)E(24)

%16 0x1000 CBE8 <-- result

b) address of (10, 15) in column major:

0x1000 BC0C + 4 * (50 * 15 + 10)
0x1000 BC0C + 4 * (760)
0x1000 BC0C + 3040

3040 in base 16 = BE0

3040 | 0 [^]
190 | 14 (E) [^]
11 | 11 (B) [^] rewrite from bottom to up
0 |

```
      1
      0x1000 BC0C
+     BE0
-----
      0x1000 C(23)EC
%16  0x1000 C7EC    <-- result
```